

**Painters Caulk**

Revision date: 26.04.2023

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Painters Caulk

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Barrier (Sealant)

1.3. Details of the supplier of the safety data sheet

Company name:	FS-BF GmbH & Co. KG	
	Division EVT Sealants	
Street:	Hahnenseifener Straße 15	
Place:	D-51580 Reichshof-Hahn	
Telephone:	+49 (0) 2297 - 9103-0	Telefax: +49 (0) 2297 1826
e-mail:	info@fsbf.com	

1.4. Emergency telephone number: 0044 (0) 797979 1298**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

2.2. Label elements**GB CLP Regulation****Precautionary statements**

P102 Keep out of reach of children.

Special labelling of certain mixtures

EUH208 Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, reaction mass of 5 -chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

Additional advice on labelling

Product does contain > 1% titanium dioxide. Due to highly viscous consistency of the product, formation of an aerosol or dust during processing is not possible. Labelling with EUH 211/212 therefore is not intended.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This article doesn't contain hazardous substances or mixtures intended to be released under normal or reasonably foreseeable conditions of use.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**



Painters Caulk

Revision date: 26.04.2023

Page 2 of 9

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
13463-67-7	titanium dioxide			0 - 2,5 %
	236-675-5		01-2119489379-17	
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one			< 0,05 %
	220-120-9	613-088-00-6		
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1; H302 H315 H318 H317 H400			
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)			< 0,0015 %
	-	613-167-00-5		
	Acute Tox. 2, Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H310 H301 H314 H318 H317 H400 H410 EUH071			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
13463-67-7	236-675-5	titanium dioxide	0 - 2,5 %
	inhalation: LC50 = > 6,8 mg/l (vapours); oral: LD50 = >5000 mg/kg		
2634-33-5	220-120-9	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	< 0,05 %
	oral: ATE = 500 mg/kg Skin Sens. 1; H317: >= 0,05 - 100		
55965-84-9	-	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	< 0,0015 %
	inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: ATE = 50 mg/kg; oral: ATE = 100 mg/kg Skin Corr. 1C; H314: >= 0,6 - 100 Skin Irrit. 2; H315: >= 0,06 - < 0,6 Eye Dam. 1; H318: >= 0,6 - 100 Eye Irrit. 2; H319: >= 0,06 - < 0,6 Skin Sens. 1A; H317: >= 0,0015 - 100 M acute; H400: M=100 M chron.; H410: M=100		

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

After contact with skin

Change contaminated, saturated clothing. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth thoroughly with water. Do NOT induce vomiting. Call a doctor if you feel unwell.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

**Painters Caulk**

Revision date: 26.04.2023

Page 3 of 9

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂). Extinguishing powder. Water spray jet. Foam. Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products.

5.3. Advice for firefighters

Use suitable breathing apparatus. Protective clothing.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Personal protection equipment: see section 8

For non-emergency personnel

No special measures are necessary.

For emergency responders

No special measures are necessary.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Take up mechanically. After curing, product can be disposed of with domestic or commercial waste. Non-cured material has to be handled as special waste.

For cleaning up

Clean with a cloth immediately. After curing, the product can be removed in most cases only mechanically.

Other information

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

Safe handling: see section 7

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Ensure sufficient ventilation.

Advice on general occupational hygiene

When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep/Store only in original container. Ensure adequate ventilation of the storage area. Avoid high temperatures or direct sunlight.



Painters Caulk

Revision date: 26.04.2023

Page 4 of 9

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance	DNEL type	Exposure route	Effect	Value
13463-67-7	titanium dioxide	Worker DNEL, long-term	inhalation	systemic	10 mg/m ³

PNEC values

CAS No	Substance	Environmental compartment	Value
13463-67-7	titanium dioxide	Freshwater	0,184 mg/l
		Marine water	0,018 mg/l
		Freshwater sediment	1000 mg/kg
		Marine sediment	100 mg/kg
		Micro-organisms in sewage treatment plants (STP)	100 mg/l
		Soil	100 mg/kg

8.2. Exposure controls**Individual protection measures, such as personal protective equipment****Eye/face protection**

Eye glasses with side protection

Hand protection

Recommended glove material: E.g. butyl gloves, nitrile gloves

Recommended glove thickness: > 0,4 mm

Permeation time (maximum wear duration): > 1 h.

Skin protection

Protective clothing.

Respiratory protection

Usually no personal respirative protection necessary.

Thermal hazards

not applicable



Painters Caulk

Revision date: 26.04.2023

Page 5 of 9

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	solid: Paste
Colour:	various
Odour:	characteristic
Odour threshold:	not determined

Test method**Changes in the physical state**

Melting point/freezing point:	not applicable
Boiling point or initial boiling point and boiling range:	not determined
Sublimation point:	not applicable
Softening point:	not determined
Flash point:	> 150 °C DIN ISO 2592
Lower explosion limits:	not applicable
Upper explosion limits:	not applicable
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value (at 20 °C):	ca. 8
Viscosity / dynamic:	not determined DIN 51550
Viscosity / kinematic: (at 40 °C)	> 1000 mm ² /s ISO 3219
Water solubility:	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density:	ca. 1,6 g/cm ³

9.2. Other information**Information with regard to physical hazard classes**

Sustaining combustion: No data available

Other safety characteristicsSolvent content: VOC: < 20 g/l (2004/42 EG)
VOC (CH): < 20 g/kg**Further Information**

not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

Stable under recommended storage and handling conditions.

10.3. Possibility of hazardous reactions



Painters Caulk

Revision date: 26.04.2023

Page 6 of 9

May form hazardous decomposition products when exposed to high temperatures.

10.4. Conditions to avoid

Avoid high temperatures or direct sunlight. Frost.

10.5. Incompatible materials

Acid. Oxidising agent, strong. Reducing agent, strong.

10.6. Hazardous decomposition products

Hazardous combustion products

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
13463-67-7	titanium dioxide				
	oral	LD50 >5000 mg/kg	Ratte		
	inhalation (4 h) vapour	LC50 > 6,8 mg/l	Ratte		
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one				
	oral	ATE 500 mg/kg			
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)				
	oral	ATE 100 mg/kg			
	dermal	ATE 50 mg/kg			
	inhalation vapour	ATE 0,5 mg/l			
	inhalation dust/mist	ATE 0,05 mg/l			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards



Painters Caulk

Revision date: 26.04.2023

Page 7 of 9

Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to humans.

Other information

No data available

SECTION 12: Ecological information**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
13463-67-7	titanium dioxide					
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50	61 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	

12.2. Persistence and degradability

Not readily biodegradable (according to OECD criteria)

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

12.4. Mobility in soil

slightly soluble

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No indication of other harmful effects.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

After curing, product can be disposed of with domestic or commercial waste. Non-cured material has to be handled as special waste.

List of Wastes Code - residues/unused products

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

List of Wastes Code - contaminated packaging



Painters Caulk

Revision date: 26.04.2023

Page 8 of 9

080410 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants other than those mentioned in 08 04 09

Contaminated packaging

The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 75

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water



Painters Caulk

Revision date: 26.04.2023

Page 9 of 9

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,9.

Relevant H and EUH statements (number and full text)

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, reaction mass of 5 -chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Further Information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)